

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
24 March 2005 (24.03.2005)

PCT

(10) International Publication Number  
**WO 2005/027266 A1**

(51) International Patent Classification<sup>7</sup>: **H01Q 3/26**

(21) International Application Number:  
PCT/GB2004/003840

(22) International Filing Date:  
8 September 2004 (08.09.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
03255736.5 12 September 2003 (12.09.2003) EP  
0321350.1 12 September 2003 (12.09.2003) GB

(71) Applicant (for all designated States except US): BAE SYSTEMS plc [GB/GB]; 6 Carlton Gardens, London, Greater London SW1Y 5AD (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): EASTON, Nicholas, John [GB/GB]; BAE SYSTEMS ATC, Sensor Systems, West Hanningfield Road, Great Baddow, Chelmsford Essex CM2 8HN (GB).


(74) Agents: ROONEY, Paul, Blaise et al.; BAE SYSTEMS plc, Group IP Department, Lancaster House, P.O. Box 87, Farnborough Aerospace Centre, Farnborough Hampshire GU14 6YU (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: OPTICAL TIME DELAY BEAM STEERING APPARATUS



(57) Abstract: Embodiments of the invention are concerned with beam steering apparatus comprising: an antenna array having a plurality of antenna elements, the antenna elements being spatially arranged with respect to one another and being operable to receive signals; signal modulating means comprising a plurality of optical modulators, each of which is associated with a different one of the antenna elements and operable to modulate signals received thereby onto a different respective optical carrier; delay means arranged to apply an amount of delay to modulated optical signals passing therethrough in respect of one or more of the antenna elements; demultiplexing means operable to separate the modulated optical carriers within an optical signal output by the delay means; demodulating means operable to demodulate the signal received by each antenna element from the respective separated modulated optical carrier; and combining means operable to combine the demodulated received signals output by the demodulating means, wherein the delay means comprise: a plurality of first delay units, each of which is associated with a different one of the antenna elements and is operable to apply selectively either a first amount of delay or a second amount of delay to the respective modulated optical signal passing therethrough; and a plurality of second delay units, each of which is linked in series to at least one of the first delay units and is operable to apply selectively either a third amount of delay or a fourth amount of delay to modulated optical signals passing therethrough, and wherein at least one of said second delay units is connected in series to at least two of the first delay units.



**Published:**

— *with international search report*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

## OPTICAL TIME DELAY BEAM STEERING APPARATUS

Field of the Invention

The present invention relates to beam steering apparatus and is suitable,  
5 particularly but not exclusively, for use with antennas arranged to transceive  
radio frequency signals.

Background of the Invention

Many different signal processing systems are faced with the problem of  
capturing signals that emanate from different directions. Examples of such  
10 systems include Radio Frequency (RF) base stations, air traffic control systems,  
and satellite systems (to name a few), which either employ mechanical devices  
comprising an antenna that physically moves in space, or electronic devices  
comprising antenna elements that apply various phase shifts to incident signals,  
thereby effectively steering the incident signal. These electronic devices are  
15 commonly referred to as phased antenna arrays and are becoming more and  
more commonly used in RF sensor and communications systems because they  
do not involve physical motion of the antenna and are capable of moving a  
beam rapidly from one position to the next.

Phased arrays are conventionally implemented by applying a phase and  
20 amplitude weight to an element of an antenna array. By altering the phase  
slope applied across the array the pointing direction of the beam can be  
controlled. Alternatively a time delay is applied to an element of an antenna  
array; an advantage of applying time delays as opposed to a phase shift is that  
time is frequency independent, whereas phase is frequency dependent (for two  
25 different frequencies, the same amount of phase is equivalent to two different  
amounts of time and thus two different beam directions; if two signals of  
different frequencies are received and processed at the same time, this same  
amount of phase will result in the beams being steered in two different  
directions).

- 2 -

Antennas that are designed to instantaneously receive signals over a broad range of frequencies typically apply an amount of time to each element instead of an amount of phase, since this enables incident beams to be steered independently of their respective frequencies. Time delay systems essentially  
5 comprise time delay units having transmission lines of varying lengths and incoming signals are passed through various lengths in order to modify the direction of the beam. Conventional systems typically include digital devices that switch in these transmission lines, effectively adding discrete time delay "bits" to the beams. A problem with these systems is that the transmission lines  
10 occupy physical space, and, for a large array of antenna elements, many different lengths of transmission lines are required, which results in bulky and costly arrangements.

#### Summary of the Invention

According to a first aspect of the present invention there is provided  
15 beam steering apparatus comprising:

an antenna array having a plurality of antenna elements, the antenna elements being spatially arranged with respect to one another and being operable to receive signals;

signal modulating means comprising a plurality of optical modulators,  
20 each of which is associated with a different one of the antenna elements and operable to modulate signals received thereby onto a different respective optical carrier;

delay means arranged to apply an amount of delay to modulated optical signals passing therethrough in respect of one or more of the antenna  
25 elements;

demultiplexing means operable to separate the modulated optical carriers within an optical signal output by the delay means;

demodulating means operable to demodulate the signal received by each antenna element from the respective separated modulated optical carrier; and

- 3 -

combining means operable to combine the demodulated received signals output by the demodulating means,

wherein the delay means comprise:

5 a plurality of first delay units, each of which is associated with a different one of the antenna elements and is operable to apply selectively either a first amount of delay or a second amount of delay to the respective modulated optical signal passing therethrough; and

10 a plurality of second delay units, each of which is linked in series to at least one of the first delay units and is operable to apply selectively either a third amount of delay or a fourth amount of delay to modulated optical signals passing therethrough,

and wherein at least one of said second delay units is connected in series to at least two of the first delay units.

15 Preferably, each optical carrier has a different frequency to that of the other carriers. This has the advantage that a number of different modulated optical carriers may pass through the same section of optical fibre without interference taking place between those carriers. Preferable the optical carriers are generated by lasers.

20 Thus in embodiments of the invention a given second delay unit is effectively re-used by a plurality of first delay units, which means that duplication of second delay units is minimised. Furthermore, different modulated optical carriers may be combined in a single optical fibre for input to a second delay unit that is linked to a number of first delays units so that each of the combined modulated optical carriers are delayed simultaneously, by a selected  
25 amount, without needing to separate the different modulated optical carriers.

In the event that the antenna array comprises a significant number of antenna units, and the delay circuitry comprises a corresponding significant number of first delay units, the delay circuitry preferably comprises further delay units arranged in series with the second delay units, and each further delay unit

- 4 -

is connected to at least two second delay units. Thus this feature of re-use of time delay units is reproduced by each set of time delay units.

In one embodiment the delay circuitry is provided by a plurality of opto-electronic switches operable to route an optical signal through different lengths of fibre optic delay line to provide selectively the required amount of delay. Such  
5 opto-electronic switches may be arranged in series with one another, and a first difference between the first and second amounts of delay is different to a second difference between the third and fourth amounts of delay. In preferred arrangements the second difference is greater than the first difference, and the  
10 signals modified by the said at least two first delay units are combined prior to further modification by the second delay unit.

In preferred embodiments of the present invention optical fibre is used as the transmission medium. This has several advantages in comparison with the prior art use of cables to convey radio frequency signals through a series of  
15 delay circuits. In particular, in using optical fibre, signal losses and dispersion effects may be reduced and the resulting apparatus provides a physically compact and stable solution that is resistant to electro-magnetic interference. In this embodiment, signals modified by the first delay units are collected into the same waveguide prior to modification by the second delay unit, and are only  
20 combined into a single output signal after when the second time delay unit has applied the third or fourth amount of time delay and the resultant signals have been demultiplexed and demodulated. The beam steering apparatus comprises a demultiplexing device, preferably a wavelength division demultiplexing device, arranged to separate out the respective modulated carriers from the waveguide,  
25 and a demodulating unit arranged to demodulate the carriers from the optical domain into the radio frequency domain, at which point the signals are combined.

According to a second aspect of the present invention there is provided a method for combining signals received by antenna elements of an antenna  
30 array, the antenna array having a plurality of said antenna elements arranged spatially with respect to one another, the method comprising the steps of:

- 5 -

- (i) for each antenna element of the array, modulating a signal received by the antenna element onto a different respective optical carrier, each said optical carrier having a different wavelength;
- (ii) passing each of the modulated optical signals through first delaying means comprising a plurality of first delay units, a different one of said plurality of first delay units being provided in respect of each antenna element to apply selectively either a first or a second amount of delay to the respective modulated optical signal passing therethrough;
- (iii) passing the modulated optical signals delayed by said first delaying means through second delaying means comprising a plurality of second delay units, wherein at least one of said second delay units is linked to at least two of said first delay units and the modulated optical signals output by said at least two of said first delay units are collected into the same optical waveguide for input to said at least one of said second delay units, each said second delay unit being arranged to apply selectively either a third or a fourth amount of delay to optical signals passing therethrough;
- (iv) separating the delayed modulated optical carriers, output by the second delaying means, in a demultiplexer;
- (v) demodulating the signal received by each of said antenna elements from the respective separated delayed modulated optical carrier; and
- (vi) combining the demodulated signals to output a combined signal as received by the antenna array.

Further features and advantages of the invention will become apparent from the following description of preferred embodiments of the invention, given by way of example only, which is made with reference to the accompanying drawings.

#### Brief Description of the Drawings

Figure 1 is a schematic diagram showing a conventional phased antenna array;

- 6 -

Figure 2 is a schematic diagram showing a first embodiment of a beamformer according to the invention;

Figure 3 is a schematic diagram showing an alternative arrangement of the beamformer of Figure 2; and

5        Figure 4 is a schematic diagram showing a second embodiment of a beamformer according to the invention.

#### Detailed Description of the Invention

Figure 1 shows a wavefront 10 incident on a beam steering apparatus implemented as conventional phased antenna array 1. In such known  
10        arrangements the antenna array 1 comprises a plurality of antenna elements 100a, 100b, 100c, 100d, each of which is arranged to apply a certain amount of time delay to the part of the wavefront impinging thereon. The amount of time delay applied by each element is dependent on the shape of the wavefront and on the angle that the wavefront makes with respect to the antenna elements  
15        (referred to herein as direction of arrival of the wavefront); as can be seen from Figure 1, different amounts of time delay are applied to each element, and the difference between the amounts of time delay applied by respective antenna elements is greatest between peripheral antenna elements 100a, 100d.

In this conventional arrangement, each antenna element 100a, 100b,  
20        100c, 100d is connected to a plurality of delay units such 101a, 103a ... 101d, 103d that are arranged in series. Note that the embodiment shown in Figure 1 is illustrative only; in practice many more antenna elements will be used. When embodied as a two way switch, at any instant of time each delay unit is arranged to apply one of two amounts of time delay – here 0 and L for first  
25        delay units 101a ... 101d, and 0 and 2L for second delay units 103a ... 103d. Thus, in this example the first and second amounts of delay are 0 and L and the third and fourth amounts of delay are 0 and 2L respectively. It should be noted that the arrangement shown in the Figure is ideal since it implies that multiples of delay L compensate precisely for corresponding multiples of D.

30        In the Figure the signal path taken through a switch is indicated by a solid line. Thus in this example the incoming wave 10 is effectively steered by

- 7 -

applying a delay of 0 to the wave received by antenna element 100a, by applying a delay of L to the wave received by antenna element 100b, by applying a delay of 2L to the wave received by antenna element 100c, and by applying a delay of 3L to the wave received by antenna element.

5           The degree of time delay control is dependent on the delay applied by the time delay units (here switches 101a ... 103d), and selection of this degree of time delay control is dependent on a minimum acceptable quality of beam shape, which is governed by the maximum time delay error that can be suffered at each element. In the example shown in Figure 1, the smallest amount of  
10 time delay that can be applied is L, so the antenna array 1 can compensate for the direction of arrival of the wavefront with an accuracy of 1L.

It will be appreciated that, as the angle between the wavefront and the antenna elements 100a ... 100d increases, the difference between the amounts of time delay applied at peripheral antenna elements 100a, 100d has to  
15 increase correspondingly. Furthermore, if the wavefront is to be steered at various positions along its length, the antenna array 1 will have to comprise many time delay units in series with one another, which means that the antenna array 1 can be quite large and complex. Moreover, if fine-tuning of the time delay control is required (meaning that the amount of delay (L) applied by the  
20 first time delay units 101a ... 101d is small), even more delay units will be required.

Embodiments of beam steering apparatus according to the invention will now be described with reference to Figures 2 and 3. Turning firstly to Figure 2, in a first embodiment of the invention, referred to herein as a beamformer, the  
25 beamformer 2 comprises a plurality of first delay units 101a ... 101d, each of which is arranged to apply an amount of time delay to signals transceived by a respective antenna element, and a plurality of second delay units 203a, 203b, each of which is arranged to apply an amount of time delay to signals that have been modified by the first delay units 101a ... 101d. At least one 203a, and  
30 preferably both 203a, 203b, of the second units are connected to two first delay units 101a, 101b via a combiner unit 205a, 205b, which, in the case of combiner unit 205a, is arranged to combine signals that have been modified by the

- 8 -

associated first delay units 101a, 101b, and in the case of combiner unit 205b, is arranged to combine signals that have been modified by the associated first delay units 101c, 101d. Preferably the combiner units 205a, 205b sum the modified signals, and pass them onto the second delay units 203a, 203b, which  
5 proceed to apply a further delay to the signals. These further modified signals are then combined in another combiner unit 207, summing the further delayed signals.

Turning again to Figure 1, it can be seen that when the antenna array 1 is applying 0, L, 2L and 3L delay to signals transceived at respective antenna  
10 elements 100a ... 100d, second switches 103a, 103b assume the same switch position as one another (in this example 2L), and second switches 103c, 103d assume the same switch position as one another (in this example 0). By use of the present invention, the duplication of delay units is reduced, which means that the antenna array includes fewer delay units. As a result, antenna arrays  
15 can be produced according to the invention, which are less bulky, complex and costly than those currently utilized.

In the example shown in Figure 2, there are only four antenna elements, and, since the first delay units 101a ... 101d are embodied as two-way switches (meaning that each combiner unit 205a, 205b receives input from two first  
20 units), the beamformer 2 only comprises two levels of delay units. However, in practical embodiments of the invention, beamformers comprise a significantly greater number of antenna elements, which means that the number of levels of delay units will increase accordingly. Figure 3 shows an example where the beamformer comprises eight antenna elements 100a ... 100h and three levels  
25 of delay units (101a ... 101h, 203a ... 203d, 209a and 209b). The improved efficiency, in terms of reduction of duplicated delay units (and corresponding re-use or "sharing" of amounts of delay) can be readily appreciated with increasing numbers of antenna elements and amounts of delay required.

In one embodiment the signals are passed between delay units 101a ...  
30 101d, 103a ... 103d and combiner units 205a, 205b via cables. However, in a further embodiment the transmission medium used is optical fibre, in order to

- 9 -

reduce relative losses and dispersion effects, and to provide a physically compact and stable solution that is resistant to electro-magnetic interference.

Figure 4 shows a further embodiment of the beam steering apparatus according to the present invention. Transceived Radio Frequency (RF) signals are in this embodiment modulated onto an optical carrier by laser devices 413a ... 413d, and the (first and subsequent) delay units 401a ... 401d, 403a ... 403d, etc. are preferably embodied in Opto Electronic Integrated Circuits (OEIC). Each transceived signal is modulated onto an optical carrier having a wavelength, for example, in the 1300 nm or in the 1550 nm band.

The summation of signals performed by respective combiner units 405a, 405b, 407 etc. can be performed in the optical domain, but more preferably is performed in the RF domain because RF signals have a far longer wavelength (thus more relaxed accuracy requirements) than that of optical carriers. In one arrangement the signals can be summed, as described above with reference to Figures 2 and 3, at each combiner unit, which involves demodulating and re-modulating the RF signals from their respective carriers at each combiner unit (meaning that the combiner units will require the corresponding modulating and demodulating capabilities). Preferably, however, the signals are merely collected by combiner units 405a, 405b in the optical domain and are only summed when the collected signals have been separated out and demodulated into the RF domain. This means that only one device is required to have demodulating capabilities.

Accordingly, in this arrangement each transceived signal is modulated onto an optical carrier of a different wavelength, and each combiner unit 205a, 205b, 207 etc. is arranged to input signals received from its associated first units 101a, 101b into the same waveguide. Wavelengths in the 1300 nm and 1550 nm bands can be used, and the wavelengths are spaced apart so that there is no interference between the carriers (e.g. spacing between 0.1 nm and 14 nm can be used). The combined signals pass through the next and, if relevant, successive delay units 403a, 403b as described above with reference to Figure 2, with identical time delays being applied to those wavelengths passing through the same delay unit. The beamformer 2 may also comprise a

- 10 -

final combiner 407 and a conventional wavelength demultiplexing device 415 that is arranged to demultiplex the wavelengths at the output using conventional wavelength demultiplexing techniques. These demultiplexed signals can then be demodulated and summed in the RF domain using a suitable device, shown  
5 as part 417.

Whilst in the above embodiments the time delay units are two-way switches, they could alternatively be switches comprising three or more switching paths. In this case, the combiner units can be arranged to receive input from a corresponding three or more first units.

10 Whilst in the second embodiment the delay units are provided by OEIC, they could alternatively be provided by suitable mechanical switches.

Whilst in the above embodiments the entire beamformer is shown to be configured in accordance with the invention, the hierarchical arrangement of first delay units and second delay units could alternatively be applied to a  
15 selected part of the beamformer.

Whilst in the above embodiments the delay unit arrangement includes one switchable delay unit at each node, the arrangement could alternatively comprise a plurality of two-way switchable delay units arranged in series at each node in at least the highest level nodes of the hierarchy (the antenna  
20 element level.) Each such a series would consist of delay units having progressively smaller time delay differences between their two respective settings (e.g.  $L$ ,  $L/2$ ,  $L/4$ , etc.), whereby a variety of time delays may be applied at selected increments (e.g.  $L/4$ ) at each element. Thus, a variety of beam steering angles may be achieved by selecting appropriate settings for each of  
25 the switches in each of the series.

Whilst in the above embodiments the combiner units 205a ... 205d, 207a, etc. are shown to be separate from respective second delay units 203a ... 203d, 209a, 209b, they could alternatively be an integral part of the second delay units.

- 11 -

Whilst in the Figures the antenna elements 100a ... 100d are shown spaced in a linear array, they could alternatively be spaced in a circular array or a planar array.

The above embodiments are to be understood as illustrative examples of the invention. It is to be understood that any feature described in relation to any one embodiment may be used alone, or in combination with other features described, and may also be used in combination with one or more features of any other of the embodiments, or any combination of any other of the embodiments. Furthermore, equivalents and modifications not described above may also be employed without departing from the scope of the invention, which is defined in the accompanying claims.

- 12 -

Claims

1. Beam steering apparatus comprising:

an antenna array having a plurality of antenna elements, the antenna  
5 elements being spatially arranged with respect to one another and being  
operable to receive signals;

signal modulating means comprising a plurality of optical modulators,  
each of which is associated with a different one of the antenna elements and  
operable to modulate signals received thereby onto a different respective optical  
10 carrier;

delay means arranged to apply an amount of delay to modulated optical  
signals passing therethrough in respect of one or more of the antenna  
elements;

demultiplexing means operable to separate the modulated optical  
15 carriers within an optical signal output by the delay means;

demodulating means operable to demodulate the signal received by each  
antenna element from the respective separated modulated optical carrier; and

combining means operable to combine the demodulated received signals  
output by the demodulating means,

20 wherein the delay means comprise:

a plurality of first delay units, each of which is associated with a  
different one of the antenna elements and is operable to apply selectively  
either a first amount of delay or a second amount of delay to the  
respective modulated optical signal passing therethrough; and

25 a plurality of second delay units, each of which is linked in series  
to at least one of the first delay units and is operable to apply selectively  
either a third amount of delay or a fourth amount of delay to modulated  
optical signals passing therethrough,

- 13 -

and wherein at least one of said second delay units is connected in series to at least two of the first delay units.

2. Beam steering apparatus according to claim 1, wherein each of said  
5 optical carriers has a predetermined wavelength that is different in respect of each antenna element.

3. Beam steering apparatus according to claim 2, wherein said demultiplexing means comprise a wavelength division demultiplexer.

10

4. Beam steering apparatus according to claim 1, 2 or 3, wherein a first difference, between the first and second amounts of delay, is different to a second difference, between the third and fourth amounts of delay.

15 5. Beam steering apparatus according to claim 4, wherein the said second difference of delay is greater than the said first difference.

6. Beam steering apparatus according to any one of the preceding claims, further comprising optical combining means arranged to combine the modulated  
20 optical signals modified by said at least two of the first delay units.

7. Beam steering apparatus according to claim 6, wherein the optical combining means are arranged to combine the modulated optical signals delayed by said at least two of the first delay units and to output the combined  
25 signal into a single optical waveguide for input to said at least one of said second delay units.

- 14 -

8. Beam steering apparatus according to any one of the preceding claims, wherein each of said first and second delay units comprise an opto-electrical switching device arranged to selectively apply respective said amounts of delay to a modulated optical carrier passing therethrough.
- 5
9. Beam steering apparatus according to any one of the preceding claims, wherein the antenna elements are spatially arranged so as to form a linear array.
- 10 10. Beam steering apparatus according to any one of the preceding claims, wherein the antenna elements are spatially arranged so as to form a circular array.
11. Beam steering apparatus according to any one of the preceding claims, wherein the antenna elements are spatially arranged so as to form a planar array.
- 15
12. A method for combining signals received by antenna elements of an antenna array, the antenna array having a plurality of said antenna elements arranged spatially with respect to one another, the method comprising the steps of:
- 20
- (i) for each antenna element of the array, modulating a signal received by the antenna element onto a different respective optical carrier, each said optical carrier having a different wavelength;
- 25 (ii) passing each of the modulated optical signals through first delaying means comprising a plurality of first delay units, a different one of said plurality of first delay units being provided in respect of each antenna element to apply selectively either a first or a second amount of delay to the respective modulated optical signal passing therethrough;

- 15 -


- (iii) passing the modulated optical signals delayed by said first delaying means through second delaying means comprising a plurality of second delay units, wherein at least one of said second delay units is linked to at least two of said first delay units and the modulated optical signals output by said at least  
5 two of said first delay units are collected into the same optical waveguide for input to said at least one of said second delay units, each said second delay unit being arranged to apply selectively either a third or a fourth amount of delay to optical signals passing therethrough;
- (iv) separating the delayed modulated optical carriers, output by the second  
10 delaying means, in a demultiplexer;
- (v) demodulating the signal received by each of said antenna elements from the respective separated delayed modulated optical carrier; and
- (vi) combining the demodulated signals to output a combined signal as received by the antenna array.

15


13. A method according to Claim 12, wherein a first difference, between the first and second amounts of delay, is different to a second difference, between the third and fourth amounts of delay.

- 20 14. A method according to Claim 13, wherein said second difference is greater than the said first difference.

1/4



2/4







FIG. 3



# INTERNATIONAL SEARCH REPORT

Int'l Application No  
PCT/GB2004/003840

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 7 H01Q3/26

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H01Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EP0-Internal

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 6 191 735 B1 (SCHINELLER EUGENE RONALD) 20 February 2001 (2001-02-20) column 3, line 44 - column 6, line 7; figures 1,2 column 6, line 57 - line 66 -----	1-14
A	US 5 414 433 A (CHANG KAICHIANG) 9 May 1995 (1995-05-09) column 5, line 28 - column 6, line 35; figures 2,5 ----- -/--	1-14

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

15 November 2004

Date of mailing of the international search report

22/11/2004

Name and mailing address of the ISA  
European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Mercier, F

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/GB2004/003840

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>RIZA N A ET AL: "PHASED-ARRAY ANTENNA, MAXIMUM-COMPRESSSION, REVERSIBLE PHOTONIC BEAM FORMER WITH TERNARY DESIGNS AND MULTIPLE WAVELENGTHS" APPLIED OPTICS, OPTICAL SOCIETY OF AMERICA, WASHINGTON, US, vol. 36, no. 5, 10 February 1997 (1997-02-10), pages 983-996, XP000685218 ISSN: 0003-6935 the whole document</p>	1-14
A	<p>US 5 721 556 A (GOUTZOULIS AKIS P) 24 February 1998 (1998-02-24) column 2, line 16 - column 4, line 60; figures 4-7</p>	1-14
A	<p>US 5 103 495 A (GOUTZOULIS ANASTASIOS P) 7 April 1992 (1992-04-07) column 3, line 35 - column 6, line 24; figure 3</p>	1-14
A	<p>US 5 977 911 A (GREEN LEON ET AL) 2 November 1999 (1999-11-02) column 8, line 16 - column 10, line 35; figure 5</p>	1-14
A	<p>DE 199 56 351 A (DAIMLER CHRYSLER AG) 31 May 2001 (2001-05-31) column 2, line 26 - column 5, line 35; figure 2</p>	1-14

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/GB2004/003840

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 6191735	B1	20-02-2001	NONE	
US 5414433	A	09-05-1995	NONE	
US 5721556	A	24-02-1998	NONE	
US 5103495	A	07-04-1992	NONE	
US 5977911	A	02-11-1999	US 6574021 B1	03-06-2003
			US 6768458 B1	27-07-2004
			US 6124827 A	26-09-2000
DE 19956351	A	31-05-2001	DE 19956351 A1	31-05-2001